SPECIFICATIONS FOR ROAD DUMP TRAILERS

	AM 480-285	AM 510-700	AM 610-1000	AM 612-1200	AM 614-1400	AM 614-1600	AM 616-1400	AM 616-2000	AM 616-2400	AM 714-1400	AM 714-1600
WEIGHT (lbs)	1350	1865	1925	2350	2650	3040	3100	3400	3600	3800	3900
BOX SIZE	4' x 8'	5' x 10'	6' x 10'	6' x 12'	6' x 14'	6' x 14'	6' x 16'	6' x 16'	6' x 16'	7' x 14'	7' x 14'
CAPACITY (GVWR)	2850	7 000	10000	12000	14000	16000	14000	20000	24000	14000	16000
AXLES	2 x 1,500 lbS	2 x 3,500 lbs	2 x 5,000 lbs	2 x 6,000 lbs	2 x 7,000 lbs	2 x 8,000 lbs	2 x 7,000 lbs	2 x 10,000 lbs double tires	2 x 12,000 lbs double tires	2 x 7,000 lbs	2 x 8,000 lbs
OVERALL LENGTH	180"	204"	204"	228"	252"	252"	276"	276"	276"	252"	252"
OVERALL WIDTH	70"	82 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"
COUPLER HEIGHT	13″	15″	15″	15″	20″	20″	20″	20″	20″	20″	20″
SIDE WALL HEIGHT	20″	20″	20″	20″	20″	20″	20″	20″	20″	20″	20″
TRACK WIDTH CENTER/CENTER	60″	72″	84″	84″	84″	84″	84″	84″			
AXLE DIAMETER	1.900″(2)	2 3/8″(2)	3″(2)	3″(2)	3″ (2)	3″ (2)	3″ (2)	3″ (3)		3″ (2)	3″ (2)
QUANTITY OF BOLTS	5	5	6	8	8	8	8	8	8	8	8
SUSPENSION BLADES	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
TIRES	175/80Dl3	225/75Dl5	225/75Dl5	235/85R16	235/85R16	235/85R16	235/85R16	235/85R16	235/85R16	235/85R16	235/85R16
TAILGATE	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door
COUPLER	2″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″
12 VOLT HYDRAULIC UNIT	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included
ELECTRIC BRAKES	Optional 7″	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD
HYDRAULIC BRAKES	N/A	N/A	N/A	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
CYLINDER	Under 3″ x 6″(I)	Under 3″ x 6″(2)	Under 3″ x16″(2)	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic

SPECIFICATIONS FOR ROAD DUMP TRAILERS

	AM 716-1400	AM 716-1600	AM 718-2000	AM 720-2000	AM 716-2000	AM 816-1400	AM 816-1600	AM 820-2000	AM 820-3000	AM 824-3000	
WEIGHT	4000	4100	4799							9766	
BOX SIZE	7' x 16'	7' x 16'	7' x 18'	7' x 20'	7' x 16'	8' x 16'	8' x 16'	8' x 20'	8' x 20'	8' x 24'	
CAPACITY (GVWR)	14000	16000	20000	20000	20000	14000	16000	20000	30000	30000	
AXLES	2 x 7,000 lbs	2 x 8,000 lbs	2 x 10,000 lbs double tires	2 x 10,000 lbs double tires	2 x 10,000 lbs double tires	2 x 7,000 lbs	2 x 8,000 lbs	2 x 10,000 lbs double tires	2 x 15,000 lbs double tires	2 x 15,000 lbs double tires	
OVERALL LENGTH	276"	276"	300"	324"	276"	276"	276"	324"	324"	385"	
OVERALL WIDTH	94 1/2"	94 1/2"	94 1/2"	94 1/2"	94 1/2"						
COUPLER HEIGHT	20″	20″	20″	20″	20″	20″	20″	20″	20″	20″	
SIDE WALL HEIGHT	20″	20″	20″	20″	20″	20″	20″	20″	20″	20″	
TRACK WIDTH CENTER/CENTER											
AXLE DIAMETER	3″ (2)	3″ (2)				3″ (2)	3″ (2)				
QUANTITY OF BOLTS	8	8	8	8	8	8	8	8	8	8	
SUSPENSION BLADES	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	
TIRES											
TAILGATE	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	Double Door	
COUPLER	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	2 5/16″	
12 VOLT HYDRAULIC UNIT	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included	
ELECTRIC BRAKES	STD	STD	STD	STD	STD	STD	STD	STD	STD	STD	
HYDRAULIC BRAKES	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	
CYLINDER	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	Telescopic	