

## LOG LOADERS GENERAL SPECIFICATIONS

<b>MODEL</b>	<b>JMS 900SR</b>	<b>JMS 110</b>	<b>JMS 130</b>	<b>JMS 130 ECONO</b>	<b>JMS 155</b>	<b>JMS 170</b>	<b>AM 190</b>	<b>AM 230</b>
Boom length	9'	11'	13'	13'	15' 5"	17'	19'	23'
Boom rotation	270	360	360	360	360	360	360	360
Max grapple opening	31"	31"	36"	31"	48"	48"	48"	56"
Min grapple opening	2"	2"	4"	4"	4"	4"	4"	4"
Grapple rotation	Continous	Continous	Continous	Continous	Continous	Continous	Continous	Continous
Rack and pinion	Double	Double	Double	Simple	Double	Double	Double	Double
Half boom capacity	1800lbs	2100lbs	1950 lbs	1950 lbs	2600 lbs	2300 lbs	3000 lbs	3500 lbs
Maximum reach	950 lbs	1600 lbs	1400 lbs	1400 lbs	1900 lbs	1300 lbs	2100 lbs	3000 lbs
Working presure	2600 PSI	2600 PSI	2600 PSI	2600 PSI	2800 PSI	2800 PSI	3000 PSI	3000 PSI
Stabilizers	Télescopic	Télescopic	Télescopic	Télescopic	Télescopic	Télescopic	Télescopic	Télescopic
Weight	720 lbs	950 lbs	1100 lbs	1100 lbs	1850 lbs	1950 lbs	1985 lbs	2300 lbs
Mounting	Bolted	Bolted	3 point hitch	3 point hitch	3 point hitch	3 point hitch	3 point hitch	3 point hitch

N.B. Mid-boom and maximum outreach capacity may vary according to the working pressure adjustment.